

Name: ni chao


Tel:+86 15052894667

WeChat: +86 15052894667

E-mail:sckjcc@163.com

Company:

Jiangsu Shenchuan Machinery Technology Co., Ltd.





概述

HIMC(C)、HIMC(Z)两个系列的磁力驱动化工流程泵,是我公司近年来开发的具有国内外领先水平的高科技环保型节能新产品,该系列的磁力驱动化工流程泵是按API685标准设计。

用途

该系列磁力驱动化工流程泵可广泛适用于化工、石油、炼化、制药、制酸、印染、食品等领域的生产过程中输送不含固体颗粒、比重不大于1.84的清洁液体,特别适用于易燃、易爆、有毒、有害、有腐蚀及贵重液态介质的输送,是理想的环保型化工设备。

特点

- 1.以静轴封取代动轴封,使泵的过流部件完全处于密封状态无泄漏。
- 2.采用特种密集型、聚磁式、推拉磁路耦合的磁力驱动装置,具有结构紧凑、体积小、转矩大、涡流小、磁传动效率高、运行稳定可靠等优点。

Summary

Two series of magnetic chemical process pumps HIMC(C),HIMC(Z) is a novel hi-tech environment-friendly energy-saving product developed by our company, integrating national and overseas leading technology, this magnetic chemical process pump is designed according to API685.

Usage

This series of magnetic chemical process pump is widely used in the fields of chemical, petroleum, refinery, acid-making, dyeing and food, to convey liquid without solid particle contained, specific gravity less than 1.84, especially applicable to convey flammable, explosive, toxic, harmful, corrosive and valuable liquid, which is an ideal environment-friendly chemical appliance.

Feature

1. Replace dynamic seal by static shaft seal to seal all overflowing parts free from leakage.
2. Adopting special magnetic driving device with concentrated flux, push-pull magnetic circuit coupling, featuring compact structure, small measurement and eddy current, hi-efficiency of magnetic driving, stable and reliable operation.

3. 拥有独特的多种磁力驱动泵轴向力平衡方法, 使得泵端运行时的轴向力近似为零, 滑动轴承和止推轴承的磨损率低、故障率低, 泵的使用周期寿命长。

4. 利用多项自有专用技术, 对磁力泵的结构及零部件进行优化设计, 并与独有的生产制作工艺相结合, 把影响磁力泵效率的各种损失降到最低限度, 从而使得磁力泵的效率与机械密封泵的效率基本相同。

5. 磁力驱动器与电机的连接形式分直联式和中间联轴器式两种, 配用功率小于30KW且输送介质温度小于80℃的磁力泵一般采用直联式结构, 配用功率大于等于30KW且输送介质温度大于等于80℃的磁力泵一般采用中间联轴器式结构。采用中间联轴器式结构的磁力泵, 对于小功率磁力泵主要是防止介质温度直接传导到电机, 对于大功率磁力泵既可防止介质温度直接传导到电机, 又便于拆卸维护保养。

性能参数

流量(Q): HIMC(c)	6-700m ³ /h
扬程(H): HIMC(c)	3-140m
HIMC(z)	3-750m ³ /h
HIMC(z)	4-250m

工作温度(T):-45-450℃

工作压力(P):2.5MPa

配用功率(N):1.1-160KW

3. In possession of unique balanced axial force with multi-magnetic force, which is approximate to zero when operation, minimize the wear and breakdown of journal bearing and thrust bearing to elongate pump service life.

4. Applying several exclusive technology, optimize design of pump structure and component, combined with unique production procedure to minimize the loss of magnetic pump efficiency, therefore, magnetic pump efficiency becomes almost identical to that of mechanical sealed pump.

5. Connection type of magnetic driving device and motor can be direct connection and mid coupling, normally, for pump with power less than 30KW used to convey media less than 80℃, we use motor direct connection, otherwise, we use mid coupling. Magnetic pump with mid coupling structure can prevent temperature of media conducting directly to motor, also convenient to disassemble and maintenance.

Performance character

Flow capacity(Q): HIMC(c)	6-700m ³ /h
Head lift: HIMC(c)	3-140m
HIMC(z)	3-750m ³ /h
HIMC(z)	4-250m

Service temperature (T):-45-450℃

Working pressure (P):2.5MPa

Power(N):1.1-160KW

HIMC(C)性能参数表(2900r/min)

HIMC(C) Table of property parameters(2900r/min)

序号 No.	型号 Model	叶轮型式 Impeller type	泵额定转速n=2900r/min Speed							
			流量Q Capacity m ³ /h	扬程 head Hm	比重 $\gamma \leq 1.00$ Density		比重 $\gamma \leq 1.35$ Density		比重 $\gamma \leq 1.84$ Density	
					电机功率及型号 Electric power and models					
					功率 Power KW	型号 Model	功率 Power KW	型号 Model	功率 Power KW	型号 Model
01	40-25-125		6.3	20	2.2	YB90L-2	3	YB100L-2	4	YB112M-2
02	40-25-160		6.3	32	3	YB100L-2	5.5	YB132S1-2	7.5	YB132S2-2
03	40-25-200		6.3	50	5.5	YB132S1-2	7.5	YB132S2-2	11	YB160M1-2
04	50-32-125		12.5	20	2.2	YB90L-2	4	YB112M-2	5.5	YB132S1-2
05	65-50-125		25	20	3	YB100L-2	4	YB112M-2	5.5	YB132S1-2
06	50-32-160	A	20	36	4	YB112M-2	5.5	YB132S1-2	7.5	YB132S2-2
		B	19	31	4	YB112M-2	5.5	YB132S2-2	7.5	YB132S2-2
		C	17	28	3	YB100L-2	4	YB112M-2	5.5	YB132S1-2
		D	15	20	2.2	YB90L-2	3	YB100L-2	4	YB112M-2
		E	13	14						
07	50-32-200	A	20	50	7.5	YB132S2-2	11	YB160M1-2	15	YB160M2-2
		B	18	48					11	YB160M1-2
		C	16	40	5.5	YB132S1-2	7.5	YB132S2-2	11	YB160M1-2
		D	15	30	4	YB112M-2	5.5	YB132S1-2	7.5	YB132S2-2
08	50-32-250	A	20	85	15	YB160M2-2	18.5	YB160L-2	30	YB200L1-2
		B	20	75					15	YB160M2-2
		C	18	65	11	YB160M1-2	15	YB160M2-2	18.5	YB160L-2
		D	15	47	7.5	YB132S2-2	11	YB160M1-2	15	YB160M2-2
09	65-40-160	A	30	34	7.5	YB132S2-2	11	YB160M1-2	15	YB160M2-2
		B	28	30	5.5	YB132S1-2	7.5	YB132S2-2	11	YB160M1-2
		C	26	26			5.5	YB132S1-2	7.5	YB132S2-2
		D	24	18	3	YB100L-2	5.5	YB132S1-2	5.5	YB132S1-2
10	65-40-200	A	34	50	11	YB160M1-2	15	YB160M2-2	18.5	YB160L-2
		B	30	48	7.5	YB132S2-2	11	YB160M1-2	15	YB160M2-2
		C	26	38	5.5	YB132S1-2	7.5	YB132S2-2	11	YB160M1-2
		D	22	30						
11	65-40-250	A	36	85	22	YB180M-2	30	YB200L1-2	45	YB225M-2
		B	34	80	18.5	YB160L-2	22	YB180M-2	37	YB200L2-2
		C	30	65	15	YB160M2-2	18.5	YB160L-2	30	YB200L1-2
		D	26	50	11	YB160M1-2	15	YB160M2-2	18.5	YB160L-2

续表
Continued Table

序号 No.	型号 Model	叶轮型式 Impeller type	泵额定转速 $n=2900r/min$ Speed									
			流量Q Capacity m ³ /h	扬程 head Hm	比重 $\gamma \leq 1.00$ Density		比重 $\gamma \leq 1.35$ Density		比重 $\gamma \leq 1.84$ Density			
					电机功率及型号 Electric power and models							
					功率 Power KW	型号 Model	功率 Power KW	型号 Model	功率 Power KW	型号 Model		
12	60-40-315	A	46	140	45	YB225M-2	55	YB250M-2				
		B	44	130	37	YB200L2-2	45	YB225M-2				
		C	40	100	30	YB200L1-2	37	YB200L2-2	37	YB200L2-2		
		D	34	80			30	YB200L1-2	37	YB200L2-2		
13	80-50-160	A	55	34	11	YB160M1-2	11	YB160M1-2	15	YB160M2-2		
		B	50	30	7.5	YB132S2-2		7.5	YB132S2-2	11	YB160M1-2	
		C	46	26	5.5	YB132S1-2	5.5	YB132S1-2	7.5	YB132S2-2		
		D	40	27			5.5	YB132S1-2	7.5	YB132S2-2		
14	80-50-200	A	65	56	18.5	YB160L-2						
		B	65	50	15	YB160M2-2	18.5	YB160L-2				
		C	50	40	11	YB160M1-2	15	YB160M2-2	18.5	YB160L-2		
		D	40	32	7.5	YB132S-2	11	YB160M1-2	15	YB160M2-2		
15	80-50-250	A	65	85	30	YB200L1-2	37	YB200L2-2	45	YB225M-2		
		B	60	80								
		C	55	65	22	YB180M-2	30	YB200L1-2	37	YB200L2-2		
		D	45	48	15	YB160M2-2	15	YB160M2-2	22	YB180M-2		
16	80-50-315	A	80	140	75	YB280S-2						
		B	75	135	55	YB250M-2						
		C	70	110	45	YB225M-2	75	YB280S-2				
		D	65	85	37	YB200L2-2	45	YB225M-2				
17	100-65-160	A	100	32	15	YB160M2-2	18.5	YB160L-2				
		B	90	30					22			
		C	90	24	11	YB160M1-2	15	YB160M2-2	18.5			
		D	80	14	5.5	YB132S1-2	7.5	YB132S2-2	11			
18	100-65-200	A	100	54	22	YB180M-2	30	YB200L1-2	37	YB200L2-2		
		B	90	50								
		C	90	40	18.5	YB160L-2	22	YB180M-2	30			
		D	70	30	11	YB160M1-2	15	YB160M2-2	18.5			
19	100-65-250	A	115	85	45	YB225M-2	55	YB250M-2	90	YB280M-2		
		B	115	75					75	YB280S-2		
		C	100	65	37	YB200L2-2	45	YB225M-2	55	YB250M-2		
		D	80	48	30	YB200L1-2	30	YB200L1-2	37	YB200L2-2		

续表 Continued Table

序号 No.	型号 Model	叶轮 型式 Impeller type	泵额定转速 $n=2900r/min$ Speed									
			流量Q Capacity m ³ /h	扬程 head Hm	比重 $\gamma \leq 1.00$ Density		比重 $\gamma \leq 1.35$ Density		比重 $\gamma \leq 1.84$ Density			
					电机功率及型号 Electric power and models						功率 Power KW	型号 Model
					功率 Power KW	型号 Model	功率 Power KW	型号 Model	功率 Power KW	型号 Model		
20	100-65-315	A	135	135	90	YB280M-2	110	YB315S-2	160	YB315L1-2		
		B	130	125								
		C	115	115	75	YB280S-2	90	YB280M-2	132	YB315M-2		
		D	110	100	55	YB250M-2	75	YB280S-2	110	YB315S-2		
		E	90	85	45	YB225M-2	55	YB250M-2	75	YB280M-2		
		F	75	70	30	YB200L1-2	45	YB225M-2	55	YB250L2-2		
21	125-80-160	A	170	30	22	YB180M-2	30	YB200L1-2	37	YB200L1-2		
		B	160	26	18.5	YB160L-2	22	YB180M-2	30	YB200L-2		
		C	150	22	15	YB160M2-2	18.5	YB160L-2				
		D	130	16	11	YB160M1-2	15	YB160M2-2	18.5	YB160M-2		
22	125-80-200	A	150	50	37	YB200L2-2	45	YB225M-2	55	YB250M-2		
		B	140	46	30	YB200L1-2	37	YB200L2-2	45	YB225M-2		
		C	130	38	22	YB180M-2	30	YB200L1-2	37	YB200L2-2		
		D	110	26	15	YB160M2-2	18.5	YB160L-2	30	YB200L1-2		
23	125-80-250	A	190	80	75	YB280S-2						
		B	180	75	55	YB250M-2						
		C	170	70	45	YB225M-2	75	YB280S-2				
		D	150	55	37	YB200L2-2	55	YB250M-2	75	YB280S-2		
		E	130	47	30	YB200L1-2	37	YB200L2-2	55	YB250M-2		
24	125-80-315	A	200	130	110	YB315S-2	160	YB315L1-2				
		B	180	125			132	YB315M-2				
		C	160	10	75	YB280S-2	90	YB280M-2	132	YB315M-2		
		D	150	75	55	YB250M-2	75	YB280S-2	90	YB280M-2		
25	125-100-200	A	200	45	45	YB225M-2	55	YB250M-2				
		B	200	40	30	YB200L1-2	45	YB225M-2	55	YB250M-2		
		C	180	30	22	YB180M-2	30	YB200L1-2	45	YB225M-2		
		D	150	25					37	YB200L2-2		
26	125-100-250	A	280	75	90	YB280M-2	110	YB315S-2	160	YB315L1-2		
		B	250	70	75	YB280S-2			132	YB315M-2		
		C	230	55	55	YB250M-2	75	YB280S-2	110	YB315S-2		
		D	200	40	37	YB200L2-2	55	YB250M-2	75	YB280S-2		
27	125-100-315	A	270	135	160	YB315L1-2						
		B	250	130	132	YB315M-2						
		C	230	100	110	YB315S-2	132	YB315M-2				
		D	200	85	75	YB280S-2	110	YB315S-2	132	YB315M-2		

HIMC(C)性能参数表(1450r/min)

HIMC(C) Table of property parameters(1450r/min)

序号 No.	型号 Model	叶轮 型式 Impeller type	泵额定转速n=1450r/min Speed									
			流量Q Capacity m ³ /h	扬程 head Hm	比重 $\gamma \leq 1.00$ Density		比重 $\gamma \leq 1.35$ Density		比重 $\gamma \leq 1.84$ Density			
					电机功率及型号 Electric power and models						功率 Power KW	型号 Model
					功率 Power KW	型号 Model	功率 Power KW	型号 Model	功率 Power KW	型号 Model		
01	50-32-160	A	11	9	1.1	YB90S-4	1.1	YB90S-4	1.5	YB90L-4		
		B	10	8								
		C	9	7					1.1	YB90S-4		
		D	6	5								
		E	6	3								
02	50-32-200	A	10	13	1.5	YB90L-4	1.5	YB90L-4	2.2	YB100L1-4		
		B	9	12					1.5	YB90L-4		
		C	8	10								
		D	8	8								
03	50-32-250	A	11	20	2.2	YB100L1-4	3	YB100L2-4	4	YB112M-4		
		B	10	19								
		C	9	15			2.2	YB100L1-4				
		D	8	11					3	YB100L2-4		
								2.2	YB100L1-4			
04	65-40-160	A	15	8	1.1	YB90S-4	1.1	YB90S-4	1.5	YB90L-4		
		B	15	7								
		C	14	6					1.1	YB90S-4		
		D	12	4								
05	65-40-200	A	16	13	1.5	YB90L-4	1.5	YB90L-4	2.2	YB100L1-4		
		B	15	12	1.1	YB90S-4						
		C	14	9			1.5	YB90L-4				
		D	12	7			1.1	YB90S-4				
06	65-40-250	A	20	21	4	YB112M-4	5.5	YB132S-4	5.5	YB132S-4		
		B	18	20	3	YB100L2-4	4	YB112M-4				
		C	16	15	2.2	YB100L1-4	3	YB100L2-4	4	YB112M-4		
		D	13	12			2.2	YB100L1-4	2.2	YB100L-4		
07	65-40-315	A	22	36	11	YB160M-4	11	YB160M-4	1.1	YB160M-4		
		B	22	32	5.5	YB132S-4						
		C	20	24	4	YB112M-4	5.5	YB132S-4				
		D	18	18			4	YB112M-4			5.5	YB132S-4
08	80-50-160	A	30	8	1.5	YB90L-4	2.2	YB100L1-4	3	YB100L2-4		
		B	26	7	1.1	YB90S-4	1.5	YB90L-4	2.2	YB100L1-4		
		C	24	6			1.1	YB90S-4				
		D	20	4					1.5	YB90L-4		
								1.1	YB90S-4			

续表 Continued Table

序号 No.	型号 Model	叶轮 型式 impeller type	泵额定转速 $n=1450r/min$ Speed											
			流量 Q Capacity m^3/h	扬程 head Hm	比重 $\gamma \leq 1.00$ Density		比重 $\gamma \leq 1.35$ Density		比重 $\gamma \leq 1.84$ Density					
					电机功率及型号 Electric power and models						功率 Power KW	型号 Model		
					功率 Power KW	型号 Model	功率 Power KW	型号 Model	功率 Power KW	型号 Model				
09	80-50-200	A	34	14	3	YB100L2-4	4	YB112M-4	5.5	YB132S-4				
		B	34	12	2.2	YB100L1-4	3	YB100L2-4	4	YB112M-4				
		C	30	10	1.5	YB90L-4	2.2	YB100L1-4	3	YB100L2-4				
		D	24	7			1.5	YB90L-4	2.2	YB100L1-4				
10	80-50-250	A	34	21	5.5	YB132S-4	5.5	YB132S-4	11	YB160M-4				
		B	30	20	4	YB112M-4								
		C	26	16	3	YB100L2-4	4	YB112M-4	5.5	YB132S-4				
		D	24	12	2.2	YB100L1-4	3	YB100L2-4	4	YB112M-4				
11	80-50-315	A	42	36	11	YB160M-4	11	YB160M-4	15	YB160L-4				
		B	42	32										
		C	40	26					11	YB160M-4				
		D	36	20										
12	100-65-160	A	50	8	2.2	YB100L1-4	3	YB100L2-4	4	YB112M-4				
		B	48	7										
		C	46	6							2.2	YB100L1-4	3	YB100L2-4
		D	38	4										
13	100-65-200	A	50	13	4	YB112M-4	4	YB112M-4	5.5	YB132S-4				
		B	46	12	3	YB100L2-4								
		C	42	10			3	YB100L2-4	4	YB112M-4				
		D	36	7	2.2	YB100L1-4	2.2	YB100L1-4	3	YB100L2-4				
14	100-65-250	A	54	21	11	YB160M-4	11	YB160M-4	11	YB160M-4				
		B	50	20	5.5	YB132S-4								
		C	46	16	4	YB112M-4	5.5	YB132S-4	5.5	YB132S-4				
		D	40	10			4	YB112M-4						
15	100-65-315	A	64	32	11	YB160M-4	15	YB160L-4	18.5	YB180M-4				
		B	61	30										
		C	56	28										
		D	54	24										
		E	50	20	5.5	YB132S-4	5.5	YB132S-4	11	YB160M-4				
		F	46	16										
16	125-80-160	A	75	8	3	YB100L2-4	4	YB112M-4	5.5	YB132S-4				
		B	70	7										
		C	70	5	2.2	YB100L1-4	3	YB100L2-4	4	YB112M-4				
		D	65	4			2.2	YB100L1-4	2.2	YB100L1-4				
17	125-80-200	A	80	12	5.5	YB132S-4	11	YB160M-4	11	YB160M-4				
		B	75	11	4	YB112M-4	5.5	YB132S-4						
		C	65	9	3	YB100L2-4	4	YB112M-4	5.5	YB132S-4				
		D	60	6			3	YB100L2-4	4	YB112M-4				

续表 Continued Table

序号 No.	型号 Model	叶轮 型式 Impeller type	泵额定转速 $n=1450r/min$ Speed									
			流量Q Capacity m^3/h	扬程 head Hm	比重 $\gamma \leq 1.00$ Density		比重 $\gamma \leq 1.35$ Density		比重 $\gamma \leq 1.84$ Density			
					电机功率及型号 Electric power and models						功率 Power KW	型号 Model
					功率 Power KW	型号 Model	功率 Power KW	型号 Model	功率 Power KW	型号 Model		
18	125-80-250	A	90	20	11	YB160M-4	11	YB160M-4	15	YB160L-4		
		B	90	19								
		C	85	17	5.5	YB132S-4	5.5	YB132S-4	11	YB160M-4		
		D	75	14								
		E	70	11								
19	125-80-315	A	100	32	15	YB160L-4	18.5	YB180M-4	30	YB200L-4		
		B	95	30			15	YB160L-4	18.5	YB180M-4		
		C	85	24					45	YB160L-4		
		D	70	18								
20	125-80-400	A	105	52	30	YB200L-4	37	YB225S-4				
		B	100	50			18.5	YB180M-4	30	YB200L-4		
		C	90	44	18.5	YB180M-4			30	YB200L-4		
		D	80	38								
		E	75	30								
21	125-100-200	A	115	11	5.5	YB132S-4	11	YB160M-4	11	YB160M-4		
		B	100	10			5.5	YB132S-4	5.5	YB132S-4		
		C	90	8								
		D	80	6								
22	125-100-250	A	130	20	15	YB160L-4			30	YB200L-4		
		B	130	18	11	YB160M-4	30	YB200L-4	15	YB160L-4		
		C	120	14			11	YB160M-4	11	YB160M-4		
		D	100	10								
23	125-100-315	A	132	32			30	YB200L-4	30	YB200L-4		
		B	120	30	18.5	YB180M-4			30	YB200L-4		
		C	100	26	15	YB160L-4	15	YB160L-4	18.5	YB180M-4		
		D	90	21								
24	125-100-400	A	150	50	45	YB225M-4	45	YB225M-4				
		B	140	48	30	YB200L-4	30	YB200L-4	45	YB225M-4		
		C	120	40					30	YB200L-4	30	YB200L-4
		D	100	30	22	YB180M-4						
25	150-125-250	A	200	20	18.5	YB180M-4	22	YB180L-4	30	YB200L-4		
		B	200	18	15	YB160L-4	18.5	YB180M-4	30	YB200L-4		
		C	190	14	11	YB160M-4	15	YB160L-4	22	YB180L-4		
		D	160	10			11	YB160M-4	15	YB160L-4		
26	150-125-315	A	200	30	30	YB200L-4	37	YB225S-4	45	YB225M-4		
		B	180	30			30	YB200L-4	37	YB225S-4		
		C	170	24	18.5	YB180M-4	30	YB200L-4	30	YB200L-4		
		D	160	18	15	YB160L-4					18.5	YB180M-4

续表 Continued Table

序号 No.	型号 Model	叶轮 型式 Impeller type	泵额定转速 $n=1450r/min$ Speed									
			流量Q Capacity m ³ /h	扬程 head Hm	比重 $\gamma \leq 1.00$ Density		比重 $\gamma \leq 1.35$ Density		比重 $\gamma \leq 1.84$ Density			
					电机功率及型号 Electric power and models							
					功率 Power KW	型号 Model	功率 Power KW	型号 Model	功率 Power KW	型号 Model		
27	150-125-400	A	220	50	55	YB250M-4	75	YB280S-4	30	YB200L-4		
		B	200	48	45	YB225M-4	75	YB280S-4	22	YB180L-4		
		C	180	46	37	YB225S-4	55	YB250M-4				
		D	170	42	30	YB200L-4	45	YB225M-4				
		E	150	36			30	YB200L-4	55	YB250M-4		
		F	150	30			37	YB225S-4				
A	320	17	22	YB180L-4			30	YB200L-4	37	YB225S-4		
B	300	15	18.5	YB180M-4	90	YB280M-4						
C	280	13										
D	260	12	15	YB160L-4	18.5	YB180M-4					75	YB280S-4
E	240	11	11	YB160M-4	15	YB160L-4						
29	200-150-315	A	380	30	45	YB225S-4	75	YB280S-4				
		B	340	26	37	YB225S-4	45	YB225M-4	132	YB315M-4		
		C	320	20	30	YB200L-4	37	YB225S-4	110	YB315S-4		
		D	300	17	22	YB180L-4	30	YB200L-4				
30	200-150-400	A	400	48	75	YB280S-4	110	YB315S-4				
		B	340	40	55	YB250M-4	75	YB280S-4	37	YB225S-4		
		C	300	34	45	YB225M-4						
		D	260	28	37	YB225S-4	45	YB225M-4				
31	200-150-500	A	420	80	132	YB315M-4						
		B	400	70	110	YB315S-4	160	YB315L1-4	55	YB250M-4		
		C	360	65			132	YB315M-4				
		D	340	50	75	YB280S-4	110	YB315S-4				
32	200-200-250	A	600	12	30	YB200L-4	37	YB225S-4	160	YB315L1-4		
		B	540	11	22	YB180L-4	30	YB200L-4	110	YB315S-4		
		C	500	10								
33	250-200-315	A	650	24	55	YB250M-4	75	YB280S-4				
		B	600	20								
		C	550	16	37	YB225S-4	45	YB225M-4	132	YB315M-4		
		D	500	13	30	YB200L-4	37	YB225S-4				
34	250-200-400	A	650	52	132	YB315M1-4						
		B	550	45	90	YB280M-4	132	YB315M-4				
		C	500	40	75	YB280S-4	110	YB315S-4				
		D	450	30	55	YB250M-4	75	YB280S-4				
35	250-200-500	A	700	75								
		B	650	65	160	YB315L1-4						
		C	550	55	110	YB315S-4	160	YB315L1-4				
		D	450	40	75	YB280S-4	110	YB315S-4				

HIMC(Z)性能参数表(2900r/min)

HIMC(Z) Table of property parameters(2900r/min)

序号 No.	型号 Model	叶轮型式 Impeller type	泵额定转速n=2900r/min Speed							
			流量Q Capacity m ³ /h	扬程 head Hm	比重 $\gamma \leq 1.00$ Density		比重 $\gamma \leq 1.35$ Density		比重 $\gamma \leq 1.84$ Density	
					电机功率及型号 Electric power and models					
					功率 Power KW	型号 Model	功率 Power KW	型号 Model	功率 Power KW	型号 Model
01	40-25-200	A	11.5	49	5.5	YB132S1-2	7.5	YB132S2-2	11	YB160M1-2
		B	10.5	42	4	YB112M-2	5.5	YB132S1-2	7.5	YB132S2-2
		C	9	36	3	YB100L-2	4	YB112SM1-2	5.5	YB132S1-2
		D	7.5	28	2.2	YB90L-2	3	YB100L-2	4	YB112M-2
		E	5.5	16	1.5	YB90S-2	1.5	YB90LS-2	2.2	YB90L-2
02	50-25-250	A	16	70	11	YB160M1-2	15	YB160M2-2	22	YB180M-2
		B	14.5	62	11	YB160M1-2	15	YB160M2-2	18.5	YB160L-2
		C	13.6	42	7.5	YB132S2-2	11	YB160M1-2	15	YB160M2-2
		D	11.3	24	5.5	YB132S1-2	7.5	YB132S2-2	11	YB160M1-2
03	50-25-315	A	20	128	30	YB200L1-2	37	YB200L2-2	55	YB250M-2
		B	18.6	116	30	YB200L1-2	37	YB200L2-2	45	YB225M-2
		C	17	99	22	YB180M-2	30	YB200L1-2	37	YB200L2-2
		D	15.7	87	18.5	YB160L-2	30	YB200L1-2	37	YB200L2-2
		E	14.5	76	15	YB160M2-2	22	YB180M-2	30	YB200L1-2
		F	13	64	11	YB160M1-2	15	YB160M2-2	22	YB180M-2
04	80-40-160	A	28	33	5.5	YB132S1-2	7.5	YB132S2-2	11	YB160M1-2
		B	25.6	29						
		C	25	22	4	YB112M-2	5.5	YB132S1-2	5.5	YB132S1-2
		D	20	16	2.2	YB90L-2	3	YB100L-2	4	YB112M-2
05	80-40-200	A	29	53	11	YB160M1-2	15	YB160M2-2	18.5	YB160L-2
		B	26	47	7.5	YB132S2-2	11	YB160M1-2	15	YB160M2-2
		C	22	39	5.5	YB132S1-2	7.5	YB132S2-2	11	YB160M1-2
		D	18	20	4	YB112M-2	5.5	YB132S1-2	7.5	YB132S2-2
06	80-40-250	A	32	78	18.5	YB160L-2	22	YB180M-2	30	YB200L1-2
		B	30	72	15	YB160M2-2	18.5	YB160L-2		
		C	24	60	11	YB160M1-2	15	YB160M2-2	18.5	YB160L-2
		D	21	47	7.5	YB132S2-2	11	YB160M1-2	15	YB160M2-2
07	80-40-315	A	42	115	37	YB200L2-2	45	YB225M-2	75	YB280S-2
		B	40	107	30	YB200L1-2			55	YB250M-2
		C	34	81	22	YB180M-2	30	YB200L1-2	45	YB225M-2
		D	29	61	15	YB160M2-2	22	YB180M-2	30	YB200L1-2
08	80-40-400	A	42	156	55	YB250M-2	75	YB280S-2	110	YB315S-2
		B	40	126	45	YB225M-2	55	YB250M-2	75	YB280S-2
		C	39	112	37	YB200L2-2	45	YB225M-2	75	YB280S-2
		D	37	85	30	YB200L1-2	37	YB200L2-2	45	YB225M-2

续表 Continued Table

序号 No.	型号 Model	叶轮 型式 Impeller type	泵额定转速 $n=2900r/min$ Speed									
			流量 Q Capacity m^3/h	扬程 head Hm	比重 $\gamma \leq 1.00$ Density		比重 $\gamma \leq 1.35$ Density		比重 $\gamma \leq 1.84$ Density			
					电机功率及型号 Electric power and models						功率 Power KW	型号 Model
					功率 Power KW	型号 Model	功率 Power KW	型号 Model	功率 Power KW	型号 Model		
09	80-50-160	A	50	34	11	YB160M1-2	15	YB160M2-2	15	YB160M2-2		
		B	45	29	7.5	YB132S2-2	11	YB160M1-2	11	YB160M1-2		
		C	38	22	5.5	YB132S1-2	7.5	YB132S2-2				
		D	31	17	3	YB100L-2	4	YB112M-2	5.5	YB132S1-2		
10	80-50-200	A	62	52	18.5	YB160L-2	22	YB180M-2	30	YB200L1-2		
		B	56	46	15	YB160M2-2	18.5	YB160L-2	22	YB180M-2		
		C	49	37	11	YB160M1-2	15	YB160M2-2	18.5	YB160L-2		
		D	43	28	7.5	YB132S2-2	11	YB160M1-2	15	YB160M2-2		
11	80-50-250	A	70	82	30	YB200L1-2	37	YB200L2-2	55	YB250M-2		
		B	66	75					45	YB225M-2		
		C	60	60	22	YB180M-2	30	YB200L1-2	37	YB200L2-2		
		D	50	45	15	YB160M2-2	18.5	YB160L-2	22	YB180M-2		
12	100-50-315	A	87	115	55	YB250M-2	75	YB280S-2	110	YB315S-2		
		B	80	100	45	YB225M-2	45	YB225M-2	90	YB280M-2		
		C	70	78	30	YB200L1-2			55	YB250M-2		
		D	57	57	22	YB180M-2	30	YB200L-2	37	YB200L2-2		
13	100-50-400	A	82	194	110	YB315S-2	160	YB315L1-2				
		B	78	175	90	YB280M-2	132	YB315M-2	160	YB315L1-2		
		C	70	140	75	YB280S-2	90	YB280M-2	132	YB315M-2		
		D	60	102	45	YB225M-2	75	YB280S-2	90	YB280M-2		
14	100-80-160	A	94	32	15	YB160M2-2	18.5	YB160L-2	30	YB200L1-2		
		B	85	28	11	YB160M1-2	15	YB160M2-2	18.5	YB160L-2		
		C	76	23			11	YB160M1-2	15	YB160M2-2		
		D	66	17	5.5	YB132S1-2	7.5	YB132S-2	11	YB160M1-2		
15	100-80-200	A	103	54	30	YB200L1-2	37	YB200L2-2				
		B	95	48	22	YB180M-2	30	YB200L1-2	37	YB200L2-2		
		C	70	38	15	YB160M2-2	22	YB180M-2	30	YB200L1-2		
		D	54	30	11	YB160M1-2	15	YB160M2-2	22	YB180M-2		
16	100-80-250	A	127	82	45	YB225M-2	75	YB280S-2	90	YB280M-2		
		B	120	76			55	YB250M-2	75	YB280S-2		
		C	105	59	30	YB200L1-2	45	YB225M-2	55	YB250M-2		
		D	87	45	22	YB180M-2	30	YB200L1-2	37	YB200L2-2		
17	100-80-315	A	141	127	90	YB280M-2						
		B	135	121	75	YB280S-2						
		C	115	97	55	YB250M-2	75	YB280S-2				
		D	90	74	37	YB200L2-2	45	YB200L2-2	75	YB280S-2		
18	100-80-400	A	171	187	160	YB315L1-2	160	YB315L1-2				
		B	159	170								
		C	135	130	90	YB280M-2						
		D	116	95	75	YB280S-2						

续表 Continued Table

序号 No.	型号 Model	叶轮 型式 Impeller type	泵额定转速 $n=2900r/min$ Speed									
			流量Q Capacity m^3/h	扬程 head Hm	比重 $\gamma \leq 1.00$ Density		比重 $\gamma \leq 1.35$ Density		比重 $\gamma \leq 1.84$ Density			
					电机功率及型号 Electric power and models						功率 Power KW	型号 Model
					功率 Power KW	型号 Model	功率 Power KW	型号 Model	功率 Power KW	型号 Model		
19	100-100-160	A	162	29	22	YB180M-2	30	YB200L1-2	37	YB200L2-2		
		B	150	24	15	YB160M2-2	22	YB180M-2	30	YB200L1-2		
		C	130	17	11	YB160M1-2	15	YB160L2-2	18.5	YB160L-2		
		D	110	12	7.5	YB132S2-2	11	YB160M1-2	15	YB160M2-2		
20	100-100-200	A	193	50	45	YB225M-2	55	YB250M-2	75	YB280S-2		
		B	180	44	37	YB200L2-2	45	YB225M-2				
		C	155	35	30	YB200L1-2	37	YB200L2-2	45	YB225M-2		
		D	135	26	18.5	YB160L-2	30	YB200L1-2	37	YB200L2-2		
21	150-100-250	A	230	79	75	YB280S-2	90	YB280M-2				
		B	218	73								
		C	190	58	45	YB225M-2	75	YB280S-2	90	YB280M-2		
		D	170	44	37	YB200L2-2	45	YB225M-2	75	YB280S-2		
22	150-100-315	A	250	126	132	YB315M-2	160	YB315L1-2				
		B	240	120								
		C	203	97	90	YB280M-2	132	YB315M-2	160	YB315L1-2		
		D	170	71	75	YB280S-2	90	YB280M-2	110	YB315S-2		
23	150-100-400	A	300	197								
		B	290	180								
		C	260	145								
		D	224	105	110	YB315S-2	160	YB315L1-2				
24	150-150-200	A	320	44	55	YB250M-2	75	YB280S-2	90	YB280M-2		
		B	300	39	45	YB225M-2						
		C	265	30	37	YB200L2-2	45	YB225M-2	75	YB280S-2		
		D	220	23	22	YB180M-2	30	YB200L1-2	45	YB225M-2		
25	150-150-250	A	390	74	110	YB315S-2	160	YB315L1-2				
		B	355	62	90	YB280M-2	110	YB315S-2	160	YB315L1-2		
		C	325	46	75	YB280S-2	90	YB280M-2	110	YB315S-2		
26	150-150-315	A	442	125								
		B	430	120								
		C	372	94	160	YB315L1-2						
		D	310	68	90	YB280M-2	132	YB315M-2	160	YB315L1-2		
27	200-200-250	A	610	72	160	YB315L1-2						
		B	580	65	160	YB315L1-2						
		C	520	47	110	YB315S-2	132	YB315M-2				
		D	470	32	75	YB280S-2	90	YB280M-2	110	YB315S-2		
28	200-200-315	A	710	122								
		B	680	114								
		C	600	87								
		D	480	65	132	YB315M-2						

HIMC(Z)性能参数表(14500r/min)

HIMC(Z) Table of property parameters(1450r/min)

序号 No.	型号 Model	叶轮 型式 Impeller type	额定转速 $n=2900r/min$ Speed													
			流量Q Capacity m ³ /h	扬程 head Hm	比重 $\gamma \leq 1.00$ Density		比重 $\gamma \leq 1.35$ Density		比重 $\gamma \leq 1.84$ Density							
					电机功率及型号 Electric power and models											
					功率 Power KW	型号 Model	功率 Power KW	型号 Model	功率 Power KW	型号 Model						
1	40-25-200	A	5.8	12	1.1	YB90S-4	1.1	YB90S-4	1.5	YB90L-4						
		B	5.4	11					1.1	YB90S-4						
		C	4.6	8.5												
		D	4	6.5												
		E	3	4												
2	50-25-250	A	7.5	18	2.2	YB100L-4	3.0	YB100L2-4	4	YB112M-4						
		B	7	16					3	YB100L2-4						
		C	6.5	11.5	1.1	YB90S-4	1.5	YB90L-4	2.2	YB100L-4						
		D	6	6.5												
3	50-25-315	A	10	32.3	5.5	YB132S-4	7.5	YB132M-4	7.5	YB132M-4						
		B	9.2	29	4	YB112M-4	5.5	YB132S-4								
		C	8.3	24.3	3	YB100L2-4			4	YB112M-4	5.5	YB132S-4				
		D	7.6	22												
		E	7.1	19.5	2.2	YB100L1-4	3	YB100L2-4	4	YB112M-4						
		F	6.4	16							2.2	YB100L1-4	3	YB100L2-4		
4	80-40-160	A	14	8	1.1	YB90S-4	1.1	YB90S-4	1.5	YB90L-4						
		B	13	7					1.1	YB90S-4						
		C	11	5.5												
		D	9.5	4.5												
5	80-40-200	A	14.5	13	1.5	YB90L-4	2.2	YB100L1-4	3	YB100L2-4						
		B	13	11.5	1.1	YB90S-4	1.5	YB90L-4	2.2	YB100L1-4						
		C	11.5	9					1.1	YB90S-4	1.5	YB90L-4				
		D	9.5	7			1.1	YB90S-4			1.1	YB90S-4				
6	80-40-250	A	16	19.5			3	YB112M-4	4	YB100L2-4	5.5	YB132S-4				
		B	15	18	2.2	YB100L2-4	3	YB100L1-4	4	YB112M-4						
		C	12.5	14	1.5	YB100L1-4	2.2	YB90L-4	3	YB100L2-4						
		D	10.5	11	1.1	YB90L-4	1.5	YB90S-4	2.2	YB100L1-4						
7	80-40-315	A	21	29	5.5	YB132S-4	7.5	YB132M-4	11	YB160M-4						
		B	20	26.5												
		C	17.5	20							4	YB112M-4	5.5	YB132S-4	7.5	YB132M-4
		D	15	15							3	YB100L2-4	3	YB100L2-4	5.5	YB132S-4
8	80-40-400	A	21	39	7.5	YB132M-4	11	YB160M-4	11	YB160M-4						
		B	20	31	5.5	YB132S-4	7.5	YB132M-4	11	YB160M-4						
		C	19	28	4	YB112M-4	5.5	YB132S-4	7.5	YB132M-4						
		D	18	21	3	YB100L2-4	4	YB112M-4	5.5	YB132S-4						
9	80-50-160	A	25	8.4	1.5	YB90L-4	2.2	YB100L1-4	2.2	YB100L1-4						
		B	22.5	7							1.5	YB90L-4				
		C	19	5.5	1.1	YB90S-4	1.1	YB90S-4	1.5	YB100L2-4						
		D	16.5	4					1.1	YB100L1-4						
10	80-50-200	A	31	13	3	YB100L2-4	3	YB100L2-4	4	YB112M-4						
		B	28.5	11.5	2.2	YB100L1-4										
		C	25	9	1.5	YB90L-4	2.2	YB100L1-4	3	YB100L2-4						
		D	22	7	1.1	YB90S-4	1.5	YB90L-4	2.2	YB100L1-4						

续表 Continued Table

序号 No.	型号 Model	叶轮 型式 impeller type	泵额定转速 $n=2900r/min$ Speed									
			流量Q Capacity m^3/h	扬程 head Hm	比重 $\gamma \leq 1.00$ Density		比重 $\gamma \leq 1.35$ Density		比重 $\gamma \leq 1.84$ Density			
					电机功率及型号 Electric power and models						功率 Power KW	型号 Model
					功率 Power KW	型号 Model	功率 Power KW	型号 Model	功率 Power KW	型号 Model		
11	80-50-250	A	35	20	4	YB112M-4	5.5	YB132S-4	7.5	YB132M-4		
		B	33	18.5								
		C	30	15	3	YB100L2-4	4	YB112M-4	5.5	YB132S-4		
		D	26	11	2.2	YB100L1-4	3	YB100L2-4	3	YB100L2-4		
12	100-50-315	A	44	28	11	YB160M-4	11	YB160M-4	15	YB160L-4		
		B	40	24	7.5	YB132M-4						
		C	35	19	5.5	YB132S-4	7.5	YB132M-4	11	YB160M-4		
		D	30	14	3	YB100L2-4	4	YB112M-4	5.5	YB132S-4		
13	100-50-400	A	41	48	15	YB160L-4	22	YB180L-4	30	YB200L-4		
		B	39	43							18.5	YB180M-4
		C	35	34	11	YB160M-4	15	YB160L-4	18.5	YB180M-4		
		D	30	25	7.5	YB132M-4	11	YB160M-4	15	YB160L-4		
14	100-80-160	A	47	8	2.2	YB100L1-4	3	YB100L2-4	4	YB112M-4		
		B	42	7							3	YB100L2-4
		C	38	5.5	1.5	YB90L-4	2.2	YB100L1-4	2.2	YB100L1-4		
		D	34	4	1.1	YB90S-4	1.1	YB90S-4	1.5	YB90L-4		
15	100-80-200	A	51	13.5	4	YB112M-4	5.5	YB132S-4	7.5	YB132M-4		
		B	47	12	3	YB100L2-4	4	YB112M-4	5.5	YB132S-4		
		C	41	9.5	2.2	YB100L1-4	3	YB100L2-4	4	YB112M-4		
		D	36	7.5	1.5	YB60L-4	2.2	YB100L1-4	3	YB100L2-4		
16	100-80-250	A	64	20	7.5	YB132M-4	11	YB160M-4	15	YB160L-4		
		B	60	19							7.5	YB132M-4
		C	52	14.5	4	YB112M-4	5.5	YB132S-4	7.5	YB132M-4		
		D	46	11	3	YB100L2-4	4	YB112M-4	5.5	YB132S-4		
17	100-80-315	A	70	33	15	YB160L-4	18.5	YB180M-4	22	YB180L-4		
		B	66	30	11	YB160M-4	15	YB160L-4				
		C	56	24			11	YB160M-4	15	YB160L-4		
		D	45	18	5.5	YB132S-4	7.5	YB132M-4	11	YB160M-4		
18	100-80-400	A	85	46	22	YB180L-4	30	YB200L-4	45	YB225M-4		
		B	80	42	18.5	YB180M-4					37	YB225S-4
		C	65	33	15	YB160L-4	18.5	YB180M-4	30	YB200L-4		
		D	53	25	11	YB160M-4	15	YB160L-4	18.5	YB180M-4		
19	100-100-160	A	81	7.2	3	YB100L2-4	4	YB112M-4	5.5	YB132S-4		
		B	73	6	2.2	YB100L1-4	3	YB100L2-4	4	YB112M-4		
		C	63	4.3	1.5	YB90L-4	2.2	YB100L1-4	3	YB100L2-4		
		D	55	3	1.1	YB90S-4	1.5	YB90L-4	2.2	YB100L1-4		
20	100-100-200	A	95	12.5	5.5	YB132S-4	7.5	YB132M-4	11	YB160M-4		
		B	90	10.5								
		C	80	8.5	4	YB112M-4	5.5	YB132S-4	7.5	YB132M-4		
		D	70	6	3	YB100L2-4	3	YB100L2-4	4	YB112M-4		

续表 Continued Table

序号 No.	型号 Model	叶轮 型式 Impeller type	泵额定转速 $n=2900$ /min Speed									
			流量Q Capacity m ³ /h	扬程 head Hm	比重 $\gamma \leq 1.00$ Density		比重 $\gamma \leq 1.35$ Density		比重 $\gamma \leq 1.84$ Density			
					电机功率及型号 Electric power and models							
					功率 Power KW	型号 Model	功率 Power KW	型号 Model	功率 Power KW	型号 Model		
21	150-100-250	A	115	20	11	YB160M-4	15	YB160L-4	18.5	YB180M-4		
		B	110	18			11	YB160M-4	15	YB160L-4		
		C	100	14	7.5	YB132M-4	11	YB160M-4	11	YB160M-4		
		D	90	10	5.5	YB132S-4	7.5	YB132M-4	7.5	YB132M-4		
22	150-100-315	A	125	31	18.5	YB180M-4	30	YB200L-4	37	YB225S-4		
		B	119	29			22	YB180L-4	30	YB200L-4		
		C	104	24	15	YB160L-4	18.5	YB180M-4	22	YB180L-4		
		D	86	17.5	11	YB160M-4	11	YB160M-4	15	YB160L-4		
23	150-100-400	A	150	48	37	45	YB225M-4		75	YB280S-4		
		B	145	44	30			YB200L-4	55	YB250M-4		
		C	130	36	22	YB180L-4	30	YB200L-4	45	YB225M-4		
		D	115	26	15	YB160L-4	22	YB180L-4	30	YB200L-4		
24	150-100-500	A	180	75	75	YB280S-4	90	YB280M-4	110	YB315S-4		
		B	167	68	55	YB250M-4	75	YB280S-4				
		C	142	53	37	YB225S-4	55	YB250M-4	75	YB280S-4		
		D	120	42	30	YB200L-4	37	YB225S-4	55	YB250M-4		
25	150-150-200	A	160	11	7.5	YB132M-4	11	YB160M-4	15	YB160L-4		
		B	152	9.5			11	YB160M-4	15	YB160L-4		
		C	140	7	5.5	YB132S-4	7.5	YB132M-4	11	YB160M-4		
		D	123	5	3	YB100L2-4	4	YB112M-4	5.5	YB132S-4		
26	150-150-250	A	195	18.5	15	YB160L-4	22	YB180L-4	30	YB200L-4		
		B	180	16			18.5	YB180M-4	22	YB180L-4		
		C	160	11.5	11	YB160M-4	11	YB160M-4	15	YB160L-4		
27	150-150-315	A	220	32.5	30	YB200L-4	45	YB225M-4	55	YB250M-4		
		B	210	30			37	YB225S-4				
		C	180	24	22	YB180L-4	30	YB200L-4	37	YB225S-4		
		D	150	17	15	YB160L-4	18.5	YB180M-4	22	YB180L-4		
28	150-150-400	A	260	51	55	YB250M-4	75	YB280S-4	110	YB315S-4		
		B	250	48			90	YB280M-4				
		C	225	38	37	YB225S-4	55	YB250M-4	75	YB280S-4		
		D	200	28	30	YB200L-4	37	YB225S-4	55	YB250M-4		
29	150-150-500	A	300	77	110	YB315S-4	132	YB315M-4				
		B	283	72	90	YB280M-4	132	YB315M-4	160	YB315L1-4		
		C	233	59	75	YB280S-4	90	YB280M-4	110	YB315S-4		
		D	208	45	45	YB225M-4	75	YB280S-4	75	YB280S-4		
30	150-150-560	A	335	104	160	YB315L1-4						
		B	315	97	132	YB315M-4						
		C	260	80	90	YB280M-4	132	YB315M-4	160	YB315L1-4		
		D	212	60	75	YB280S-4	90	YB280M-4	110	YB315S-4		

续表

序号 No.	型号 Model	叶轮型式 Impeller type	泵额定转速 $n=2900r/min$ Speed									
			流量Q Capacity m ³ /h	扬程 head Hm	比重 $\gamma \leq 1.00$ Density		比重 $\gamma \leq 1.35$ Density		比重 $\gamma \leq 1.84$ Density			
					电机功率及型号 Electric power and models							
					功率 Power KW	型号 Model	功率 Power KW	型号 Model	功率 Power KW	型号 Model		
31	150-150-630	A	360	115								
		B	338	105.5								
		C	274	82	132	YB315M-4	160	YB315L1-4				
		D	220	60	90	YB280M-4	110	YB315S-4	160	YB315L1-4		
32	200-200-250	A	305	17.5	22	YB180L-4	30	YB200L-4	45	YB225M-4		
		B	290	16	18.5	YB180M-4			37	YB225S-4		
		C	260	12	15	YB160L-4	18.5	YB180M-4	30	YB200L-4		
		D	240	8	11	YB160M-4	15	YB160L-4	15	YB160L-4		
33	200-200-315	A	350	30	45	YB225M-4	55	YB250M-4	75	YB280S-4		
		B	340	29	37	YB225S-4			37	YB225S-4	55	YB250M-4
		C	300	22	30	YB200L-4	37	YB225S-4	55	YB250M-4		
		D	250	15	18.5	YB180M-4	22	YB180L-4	30	YB200L-4		
34	200-200-400	A	426	50	90	YB280M-4	110	YB315S-4	160	YB315L1-4		
		B	410	47	75	YB280S-4			132	YB315M-4		
		C	370	36.5	55	YB250M-4	75	YB280S-4	110	YB315S-4		
		D	330	27	45	YB225M-4	55	YB250M-4	75	YB280S-4		
35	200-200-500	A	495	84								
		B	470	79	160	YB315L1-4						
		C	400	63	110	YB315S-4	160	YB315L1-4				
		D	330	48	75	YB280S-4	90	YB280M-4	132	YB315M-4		
36	200-200-560	A	540	105								
		B	510	98								
		C	440	81	160	YB315L1-4						
		D	350	62	110	YB315S-4	132	YB315M-4				
37	200-200-630	A	580	132								
		B	550	125								
		C	468	100								
		D	372	75	132	YB315M-4						
38	250-250-315	A	545	27					110	YB315S-4		
		B	528	25	55	YB250M-4	75	YB280S-4	90	YB280M-4		
		C	480	19	37	YB225S-4	55	YB250M-4	75	YB280S-4		
		D	434	13	30	YB200L-4	37	YB225S-4	45	YB225M-4		
39	250-250-400	A	660	49	132	YB315M-4	160	YB315L1-4				
		B	630	46	110	YB315S-4						
		C	565	36	75	YB280S-4	110	YB315S-4	160	YB315L1-4		
		D	500	24	55	YB250M-4	75	YB280S-4	90	YB280M-4		

说明：表中有流量、扬程值而无功率值的泵，需订货时当面确定。